

VISION·3

L I G H T I N G

New Product Notice

DL1 COB LED Down Light

Precision machined aluminum or brass LED down lighting fixture available with 12V Integral Driver COB LED or Remote Driver COB LED light engines. Modular industry standard components allow for simple field replacement and future upgrades. Wet or dry location capable and certified for ceiling mount applications, the DL1 Down Light fixture is perfect for all interior, exterior, residential, commercial, retail, and hospitality uses.



Features¹

- Industry standard COB LED components and wiring connectors used to simplify maintenance and future upgrades.
- Field replaceable optics, COB, and driver.
- Available in round and square shapes.
- Available with various standard mount, cap, and stem options.
- MR16 halogen, retro-fit MR16 LED, and amber turtle safe LED lamps also available.
- Thick walled cap, optimized high temperature silicone O-ring placement, and molded silicone fixture lead seal to prevent leaking.
- Tested and certified for wet or dry location use in interior or exterior ceiling mount applications.

Specifications¹

Integral Driver COB LED

- Input voltage: 12VAC
- Lumen Output (nominal)²: 400lm, 700lm, 1000lm.
- Optics: 15°, 24°, 36°, 55°, 65°.
- CCT: 2700K, 3000K, 3500K, 4000K.
- CRI: 80, 90.
- L70 > 40,000 hours.
- Dimming³: ELV & MLV phase dimming.

Remote Driver COB LED

- Lumen Output (nominal)²: 1600lm @ 350mA,
- Optics: 15°, 24°, 36°, 55°, 65°.
- CCT: 2700K, 3000K, 3500K, 4000K.
- CRI: 80, 90.
- L70 > 40,000 hours.

1. Features and Specifications subject to change without notice. Please see latest specification sheet(s) on website for latest information.
2. Lumen Output (nominal) is ideal lumen output of light engine only in lab conditions. Actual fixture output will vary with fixture/cap type, material, lens/optics options, CRI, CCT, mounting, orientation, and environmental conditions. For more accurate information, see fixture photometry files on website.
3. Contact Vision3 for dimmer compatibility and dimming range.

