

New Product Notice

DL3 COB LED Ring Mount

Precision machined aluminum or brass LED ring mounted down lighting fixture available with 12V Integral Driver COB LED light engine. Modular industry standard components allow for simple field replacement and future upgrades. Wet or dry location capable and certified for ceiling mount applications, the DL3 Ring Mount Down Light fixture is perfect for all interior, exterior, residential, commercial, retail, and hospitality uses.



Features¹

- Industry standard COB LED components and wiring connectors used to simplify maintenance and future upgrades.
- Field replaceable optics, COB, and driver.
- MR16 halogen, retro-fit MR16 LED, and amber turtle safe LED lamps also available.
- Available with various standard cap options.
- Threaded cap for tool-less removal during maintenance.
- Thick walled cap, high temperature silicone O-ring, and molded silicone fixture lead seal to prevent leaking.
- Ring mount can be used for tree, gazebo, pergola, or cable mounted down lighting.
- Tested and certified for wet or dry location use in interior or exterior ceiling mount applications.

Specifications¹

Integral Driver COB LED

- Input voltage: 12VAC
- Lumen Output (nominal)²: 400lm, 700lm, 1000lm.
- Optics: 15°, 24°, 36°, 55°, 65°.
- CCT: 2700K, 3000K, 3500K, 4000K.
- CRI: 80, 90.
- L70 > 40,000 hours.
- Dimming³: ELV & MLV phase dimming.

1. Features and Specifications subject to change without notice. Please see latest specification sheet(s) on website for latest information.
2. Lumen Output (nominal) is ideal lumen output of light engine only in lab conditions. Actual fixture output will vary with fixture/cap type, material, lens/optics options, CRI, CCT, mounting, orientation, and environmental conditions. For more accurate information, see fixture photometry files on website.
3. Contact Vision3 for dimmer compatibility and dimming range.