Job: Approval: Type:

## LIGHTING

## In Grade Stake Mount MODEL MO2

Ø3 1/2" Stake Mount

## **Specifications:**

Housing: Housing made from corrosion resistant, thermoplastic PVC, with a black anodized machined 6061-T6 aluminum collar. Housing supplied with three integral 1/2" slip fittings for conduit connection, leak proof cable entry, and feed through wiring. (Conduit and cable not included).

Cap: Available in machined 6061-T6 aluminum, machined C36000 brass, or cast C84400 bronze. Cap contains a 1/2" NPS threaded mounting hole, and is locked to housing collar with three 18-8 stainless steel set screws.


Stem: Stems are machined from 6061-T6 aluminum or C36000 brass, and are threaded 1/2" NPS on both ends. Stem option available in lengths of 3", 6", 12", 18", 24", 30", 36", 42", and 48".


Seals: O-ring groove on cap allows for use of an O-ring to prevent leaking between cap and fixture knuckle. (Note: All Vision3 fixtures come with a high temperature, black Viton O-ring on the knuckle for this purpose). Silicone Oring between cap and junction collar ensures a watertight junction housing.


Electrical: Three integral 1/2" slip fittings allow for conduit connection, cable entry, and feed through wiring. (Conduit and cable not included).

Finish: TGIC thermo set polyester powder coat paint available in 14 standard colors. On aluminum model, finish is applied over a corrosion resistant, hexavalent chromium free, RoHS compliant coating. Aluminum model available in one additional metal finish: Clear Anodized. Machined brass model available in three additional metal finishes: Natural, Polished, and Aged. Cast Bronze model available in two additional metal finishes: Natural and Aged.

Certification: CSA tested & certified to US and Canadian safety standards for wet location landscape use per UL1598 & CSA C22.2 No. 250-08.









## Ordering Information:

		— S4-12 - Style	— 0 - Transformer	— Stem <sup>3</sup>		
MO2A - Aluminum Cap	BL - Black	<b>S4-12</b> - 12" Junction				
MO2B - Brass Cap (Machined Finish)				3 - 3" Stem		
MO2C - Bronze Cap (Cast Finish)	BN - Bronze			6 - 6" Stem		
,	BNT - Textured Bronze			12 - 12" Stem		
	BAT - Textured Bark			18 - 18" Stem		
	WI - White			24 - 24" Stem		
	GRT - Textured Green			30 - 30" Stem		
	SI - Silver			36 - 36" Stem		
	GY - Grey			<b>42</b> - 42" Stem		
	BE - Beige			48 - 48" Stem		
	GNT - Textured Granite					
	SAT - Textured Sand					
	PAT - Textured Patina		Notes:			
	EAT - Textured Earth CLA - Clear Anodized (MO2A only) NAT - Natural (MO2B & MO2C only) POL - Polished (MO2B only)			ns. certifications. a	and ordering information are	subject to change.
					specification sheets.	,
					match the model to the fixture	e it is being used with.

POL - Polished (MO2B only)

AGE - Aged (MO2B & MO2C only)

Example: MO2C - AGE - S4-12 - 0 - 0

models MO2A and MO2B.

Use MO2A with cast or machined aluminum fixtures. Use MO2B with machined

finish brass/bronze fixtures. Use MO2C with cast finish bronze fixtures. 3. Because of the machined surface finish on stems, they should only be used with