

# VISION<sup>3</sup>

L I G H T I N G

## New Product Notice

### PA5 COB LED Step Light (Box Mount)

Precision machined aluminum, brass, or stainless steel LED step light fixture with 12V Integral Driver COB LED light engine. Modular industry standard components allow for simple field replacement and future upgrades. Wet or dry location capable and certified for wall mount applications, the PA5 Step Light is perfect for all residential, commercial, retail, and hospitality uses.



#### Features<sup>1</sup>

- Industry standard COB LED components and wiring connectors used to simplify maintenance and future upgrades.
- Field replaceable optics, COB, and driver.
- Cast box and octagonal box mounting options.
- Available in round and square shapes.
- Machined covers and cutoffs come in multiple styles that can be interchanged and configured as desired.
- Covers and cutoffs rotate so that glare can be better controlled on sloped walkways or steps and for final leveling alignment.
- MR16 halogen, retro-fit MR16 LED, and amber turtle safe LED lamp options also available.
- Tested and certified for wet location use in wall mount applications.

#### Specifications<sup>1</sup>

##### Integral Driver COB LED

- Input voltage: 12VAC
- Lumen Output (nominal)<sup>2</sup>: 400lm, 700lm, 1000lm.
- Optics: 15°, 24°, 36°, 55°, 65°.
- CCT: 2700K, 3000K, 3500K, 4000K.
- CRI: 80, 90.
- L70 > 40,000 hours.
- Dimming<sup>3</sup>: ELV & MLV phase dimming.

1. Features and Specifications subject to change without notice. Please see latest specification sheet(s) on website for latest information.  
2. Lumen Output (nominal) is ideal lumen output of light engine only in lab conditions. Actual fixture output will vary with fixture/cap type, material, lens/optics options, CRI, CCT, mounting, orientation, and environmental conditions. For more accurate information, see fixture photometry files on website.  
3. Contact Vision3 for dimmer compatibility and dimming range.