

New Product Notice

PA7 LED Bollard Path Light

Precision cast bronze LED bollard light fixture with 12V Integral Driver COB LED light engine. Modular industry standard components allow for simple field replacement and future upgrades. Wet location capable and certified for landscape applications, the PA7 Bollard Path Light is perfect for all residential, commercial, retail, and hospitality uses.



Features¹

- Industry standard COB LED components and wiring connectors used to simplify maintenance and future upgrades.
- Field replaceable optics, COB, and driver.
- Available with surface mount or landscape stake mount options.
- Cast faceplate and cover with hardware concealed on the sides provides a clean, architectural appearance.
- Covers rotate so that glare can be better controlled on sloped walkways or steps and for final leveling alignment.
- MR16 halogen, retro-fit MR16 LED, and amber turtle safe LED lamp options also available.
- Tested and certified for wet location use in landscape mount applications.

Specifications¹

Integral Driver COB LED

- Input voltage: 12VAC
- Lumen Output (nominal)²: 400lm, 700lm, 1000lm.
- Optics: 15°, 24°, 36°, 55°, 65°.
- CCT: 2700K, 3000K, 3500K, 4000K.
- CRI: 80, 90.
- L70 > 40,000 hours.
- Dimming³: ELV & MLV phase dimming.

1. Features and Specifications subject to change without notice. Please see latest specification sheet(s) on website for latest information.
2. Lumen Output (nominal) is ideal lumen output of light engine only in lab conditions. Actual fixture output will vary with fixture/cap type, material, lens/optics options, CRI, CCT, mounting, orientation, and environmental conditions. For more accurate information, see fixture photometry files on website.
3. Contact Vision3 for dimmer compatibility and dimming range.